

Aurora

by Jean Ann Wright

Sewing continued:

6. Sew the remaining fabric D sashing strips rows. Each row will have (3) fabric D sashing strips and (4) fabric E sashing squares. Make 4 rows.
7. Alternate the (4) sashing rows with the (3) block rows to complete the center of the quilt top.
8. Center and sew the fabric C borders to each side of the quilt with an equal amount of border fabric overlapping at each end. Miter the corners and trim away excess fabric.

Finishing:

9. Layer the quilt top, batting and backing. Baste, then quilt the layers together.
10. Sew the binding strips together end-to-end, fold over lengthwise and sew to quilt top. Turn binding to back of quilt and stitch in place.



Featuring Fabrics from the
Aurora Collection by Ann Griffin

Be sure to visit www.windhamfabrics.com to the complete collection
and to download this and other free projects.

 Windham Fabrics

812 Jersey Ave ~ Jersey City, NJ 07310 ~ 201.659.0444 ~ info@windhamfabrics.com

 Windham Fabrics
a division of Baum Textile Mills

Aurora

Quilt designed by Jean Ann Wright
Aurora Fabric Collection by Anna Griffin

Skill Level: Intermediate
Finished Quilt size: 80" x 80"
Block Count & Size: 9 blocks 16" square

Fabric Requirements:

Fabric A 1-1/4 yd SKU # 29553-1
Fabric B 1 yd SKU # 29555-1
Fabric C 1-3/4 yd SKU # 29556-9
Fabric D 1-1/2 yd SKU # 29557-6
Fabric E 1/3 yd SKU # 29558-1
Fabric F 1-1/2 yd SKU # 29559-10
Fabric G 1 yd SKU # 29560-9

Backing: 5 yds fabric SKU # 29560-9 cut in half and sewn together selvage-to-selvage. Trim to 84" square.

Binding: 2/3 yd Fabric D, cut (9) 2-1/4" strips and sewn together end-to-end.

Materials: Fusible web for applique

Cutting:

Fabric A (9) fussy cut 8" circles (use fusible web according to manufacturer's directions).

Fabric B (3) 9-1/4" x width of fabric (wof) strips, recut (9) 9-1/4" squares, then cut squares on diagonal twice for (4) triangles from each square.

Fabric C (8) 6-1/2" x wof strips fussy cut on roses, sew together end-to-end, then cut (4) 81-1/4" borders.




Fabric D (3) 16-1/2" x wof strips, recut into (24) 4-1/2" x 16-1/2" sashing strips.

Fabric E (2) 4-1/2" x wof strips, recut into (16) 4-1/2" squares.
Fabric F (3) 8-7/8" x wof strips, recut into (18) 8-7/8" squares, then recut into (36) triangles. Cut (7) 2-1/2" x wof strips. Sew together end-to-end, then cut (2) 64-1/2" vertical borders and (2) 68-1/2" horizontal borders.

Fabric G (3) 9-1/4" x wof strips, recut (9) 9-1/4" squares, then cut squares on diagonal twice for (4) triangles from each square.

Sewing:

1. Sew a fabric B triangle to a fabric G triangle along the short sides. Make 36.
2. Sew triangles B/G to triangle F to make a square. make 36.
3. Sew 4 squares together to make double pinwheel block. Make 9. See Diagram below



4. Following manufacturer's directions fuse then applique a fussy cut fabric A circle to the center of each of the squares made in steps 1 through 3.



5. Sew the blocks together in rows of 3 blocks each, separating the blocks with a fabric D sashing strip.